

Technical Fact Sheet



Pacesetter Coated Digital

Pacesetter Coated delivers consistently reliable press performance. With exceptional print quality at a competitive price, the Pacesetter family of products will meet even the most demanding budgets.



Application Text

- Annual reports
- Brochures
- Catalogues
- Certificates
- Desk pads
- Direct Mail

Technical Fact Sheet



- Flyers
- Stationary

Features

- Available in gloss and satin
- Excellent whiteness and brightness
- Excellent press performance
- FSC® Certified (licensed code FSC® C010628)
- Dry Toner Compatible

Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Technical Fact Sheet



Printing Tips

We always recommend that the sheet is test and trialled before commencing a print job. This is to determine that the sheet is suitable for the particular machine and the particular print job.

Environmental Credentials

Download our Environmental Fact Sheet.

[Download the Pacesetter Gloss Low Carbon Certificate.](#)

FSC® Certified printers:

Pacesetter Coated is an FSC® Mix Certified paper, which ensures that all virgin pulp is derived from well-managed forests and controlled sources. It contains elemental chlorine free bleached pulp and is manufactured by an ISO 14001 certified mill.

Pacesetter Coated is made from elemental chlorine free bleached pulp sourced from well-managed forests and controlled sources. It is manufactured by an ISO 14001 certified mill.

Technical Fact Sheet



Print Process

- Die cutting
- Scoring
- Laminating
- Folding
- Varnishing
- Embossing
- Foiling
- Digital
- Creasing

Technical Fact Sheet



Technical Data

Substance	"Basis Weight (g/m2)"	"Thickness (µm)"	"Smoothness (sec)"	Roughness Mm)	Paper Gloss (%)	"Whiteness (%)"	"Brightness (%)"	"Opacity (%)"	"Bulk (cm3/g)"
113	113±4%	90±3	5000↑	0.6±0.3	75±3	120±10	92±2	95±2	0.8
128	128±4%	100±3	5000↑	0.6±0.3	75±3	120±10	92±2	97±2	0.78
148	148±4%	123±3	5000↑	0.6±0.3	75±3	120±10	92±2	98±2	0.83
170	170±4%	143±5	5000↑	0.6±0.3	75±3	120±10	92±2	98±2	0.84
200	200±4%	178±3	3000↑	0.9±0.3	72±3	120±10	91±2	98±2	0.89
250	250±4%	235±3	2000↑	1.2±0.3	72±3	120±10	91±2	99±2	0.94
300	300±4%	290±5	1700↑	1.2±0.3	70±3	120±10	91±2	99±2	0.96
350	350±4%	342±3	1700↑	1.2±0.3	70±3	120±10	91±2	99±2	0.97