

Technical Fact Sheet



Pro-Design

A high white sheet designed for high quality, professional colour copying. Compatible with dry toner and designed for high quality colour copy work. Available in A4, A3 and SRA3.



Size Availability

90gsm A4, A3, SRA3

100gsm A4, A3, SRA3

Technical Fact Sheet



120gsm A4, A3 SRA3

160gsm SRA3

200gsm SRA3

250gsm SRA3

300gsm SRA3

350gsm SRA3

Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Technical Fact Sheet



Features

- High whiteness and smoothness for a superior print finish
- Dry Toner compatible
- High whiteness and smoothness
- FSC® mix certified
- Suitable for processes such as cutting, stapling, perforating, folding, binding, laminating and sealing

Technical Fact Sheet



Technical Data

	90 g/m ²	100 g/m ²	120 g/m ²	160 g/m ²	200 g/m ²	250 g/m ²	280 g/m ²	300 g/m ²	350 g/m ²
CIE Whiteness (ISO 11475)	168	168	168	168	168	168	168	168	168
Opacity % (ISO 2471)	min 92	min 95	min 95	min 96	min98	min 98	min 98	min 99	min 99
Thickness μm (ISO 534)	98	109	125	158	196	250	280	300	350
Smoothness Bekk (sec) (ISO 5627)	130	140	140	140	135	100	80	75	75
Formation (Kajaani Index)	110	110	110	110	110	110	110	110	110
Stiffness MD/CD (ISO 2493)	125/65	165/85	255/145	455/260	700/400	1060/640	1380/800	1500/940	2900/1800

Technical Fact Sheet

