

Technical Fact Sheet



Manter Tintoretto Gesso H+O Ultra

Manter Tintoretto Gesso H+O Ultra is a wet strength natural, pure cellulose paper, felt textured on both sides with a special treatment that ensures high opacity in wet conditions. Facestock is FSC® certified (licensed code FSC® C010628).



Features

- Water-based permanent acrylic adhesive
- Good adhesion to wet surfaces at low temperatures
- Especially designed for glass containers, with excellent resistance to immersion in water/ice
- FSC® certified (licensed code FSC® C010628)
- Product specially designed for high added value bottled in glass (wine, liquors, oil, water)

Technical Fact Sheet



Application Text

Recommended for wine label production where a slight felt finish embossing is preferred. Produced with wet strength fibre composition for performance in ice/water bucket, and areas where condensation is high.

Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Backing

CB80 Super calendared white glassine paper

Backing paper designed for automatic label generation

Technical Fact Sheet



Properties	Result
Grammage	78 gsm
Caliper	67 microns

Technical Fact Sheet



Technical Data

Face Material:

Properties	Test Method	Result
Grammage	g/m ²	115 g/m ²
Caliper	Micron	150 microns
Opacity (dry/wet)	%	90 / 77
Opacity variation	%	14
Tear strength	KN/m	6,2/2,7

Adhesive:

SH 6020 Plus Permanent Acrylic Adhesive

Permanent acrylic adhesive. Strong Initial adhesion, high tack and good cohesion. Suitable for all-purpose applications on wet surfaces at low temperatures. Excellent resistance to ice water.

Properties	Test Method	
Tack	FTM 9	> 12
Cohesion	(h) 1kg FTM 8	> 2
Application temperature (min)	°C	> +5°C
Service temperature (min)	°C	> -10°C
Service temperature (max)	°C	75°C

Technical Fact Sheet

