

Technical Fact Sheet



Kantac Mirrorkote C58

Kantac Mirrorkote C58 is a cast-coated self-adhesive label stock with a mirror-like gloss surface and C58 adhesive, delivering premium printability for offset and digital label applications. Available in roll and sheet formats, it is ideal for premium product labels, cosmetics, beverages, and retail packaging.



Application Text

- Prestige point of sale labels for household goods and cosmetic packaging
- Eye catching wine labels to best represent the wine inside the bottle
- High Class beverage and food stuff labelling where a lasting crisp finish lends itself to the image of the product

Technical Fact Sheet



Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Print Process

Mirorkote accepts most common forms of printing processes including rotary and flat bed letterpress, flexography and offset. Mirorkote also die-cuts and hot stamps excellently.

Backing

Technical Fact Sheet



Backing:

DG7W

White glassine backing, convenient for the high speed printing and stripping of both rotary and flat bed letterpress labels. Its thickness, stability and hardness ensures excellent performance with label printing machines and automatic applicators.

Properties	Test Method	Result
Grammage		72gsm
Caliper	ISO 534	62microns
Tensile Strength MD		Min 7.0kg/15mm
Tensile Strength CD		Min 4.5kg/15mm

Technical Fact Sheet



Features

- High gloss white cast coated paper
- Mirror finish provides ideal contrast and brilliance for a multitude of label uses
- High quality, multi-coloured labels, with exceptional mechanical and humidity resistance.
- FSC® Certified (licensed code FSC® C010628)

Technical Fact Sheet



Technical Data

Face Material:

Properties	Test Method Result	
Grammage	ISO 536	85 ± 5 g/m ²
Caliper	ISO 534	94 ± 5 microns
Tensile Strength MD		Min 5.0kg/15mm
Tensile Strength CD		Min 3.5kg/15mm
Smoothness Bekk 5/10ml		190 ± 50