

Technical Fact Sheet



Stickler TT Matt S13

Stickler TT Matt S13 is a two-sided high-quality woodfree machine-coated matt white label paper with S13 adhesive, designed for thermal transfer and laser label printing. Offering a crisp matt finish and reliable adhesion, it is ideal for product labels, commercial labelling, and packaging applications.



Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Technical Fact Sheet



Storage

The substrate should be free of dust and lubricant before apply. Please use once unwrapped, if stock is to be returned to the storage shelf please ensure stock is wrapped and bagged to prevent surface dust and contamination. This product should be tested thoroughly under use condition to ensure it meets the requirements of the specific application.

Print Process

Designed for high quality colour printing and thermal transfer work

Backing

White Glassine - I WG white glassine backing allows high speed conversion and consistent dispensing on a wide range of equipment.

Properties Test Method Result

Grammage ISO 536	62 gsm
------------------	--------

Technical Fact Sheet



Caliper ISO 534 53 microns

Opacity ISO 2471 60%

Technical Fact Sheet



Technical Data

Face Material:

Technical Fact Sheet



Properties Test Method Result

Grammage ISO 536 82 g/m²

Caliper ISO 534 72 microns

Adhesive: S-Type – Permanent Acrylic

S-Type is a permanent acrylic adhesive, emulsion water based, offering a perfect combination of initial tack and strong adhesive, with outstanding adhesion to most substrates including rough surfaces. S-Type is a strong, multi-purpose adhesive suitable for high converting speeds, achieving optimal dispensing. Recommended for use on smooth and curved substrates with a diameter $\geq 25\text{mm}$. The adhesive complies with FDA regulation in 21 C.F.R. Section 175.105 for indirect contact applications as the label is intended for use on the outside of food packaging material.

Properties	Test Method	Result
Peel adhesion (N/25mm)	FTM 1	12.7