

Technical Fact Sheet



Stickler LaserJet RP1001 60

Stickler LaserJet is a smooth white woodfree paper, designed for traditional systems and laser printing, for A4 sheets.



Application Text

For EDP labels. Good planarity for laser printing and photocopy machines.

Technical Fact Sheet



Printing Tips

Printable with traditional systems and laser, for A4 sheets.

Testing for suitability between media, printers and inks is always recommended prior to use.

Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Storage

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following STORAGE CONDITIONS:

- This material must be stored at a temperature of $22^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and $50 \pm 5\%$ of Relative Humidity.
- Storage area must be dry and clean.

Technical Fact Sheet



- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

Backing

Kraft 1/side clay coated kraft backing for good lay flat properties.

Properties	Result
Grammage	55 gsm
Caliper	58 microns

Technical Fact Sheet



Technical Data

Face Material:

White smooth woodfree paper. FSC certified.

Technical Fact Sheet



Type	Smooth paper
Colour and Finish	White
Weight	70 g/m ² ±10% ISO-536
Thickness	89 µ ±10% ISO 534-80

Adhesive:

Rubber based permanent adhesive with high tack and adhesion on difficult and apolar (like PE and PP) substrates. RP3000 adhesive combines the rubber based properties with high speed conversion.

Reference	RP3000
Type	Rubber permanent
Min. Appl. Temp.	+5°C
Service Temp.	-30°C / +80°C
Shear	Very High
Tack	18 N/25mm FINAT FTM9
Final Adhesion	8 N/25mm FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV.