

Technical Fact Sheet



Ace Screenboard

A twin sided display board intended primarily for screen printing, the triple coated surface provides superior printing characteristics. Ace Screenboard also has outstanding bulk, thickness and stiffness qualities.



Features

- Premium, high white, twin sided display board
- Super smooth surface enhances print results
- Very rigid and dimensionally stable board with a white centre
- Outstanding bulk, thickness and stiffness qualities
- FSC® Certified (licensed code FSC® C010628)
- Fully Recyclable (kerbside)

Technical Fact Sheet



- Biodegradable
- HP Certified for Latex inks

Environmental Credentials

[Download our
Environmental Fact Sheet.](#)

Spicers Key Icons

[Download Spicer's icons](#)

Application Text

Technical Fact Sheet



- Counter cards
- POS
- Promotional cards
- Hanging Signs

Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Print Process

- Screen and UV ink curable
- Also suitable for offset printing in lower substances

Technical Fact Sheet



Size Availability

Colour	Um's	GSM
White	1, 1.5, 2, 2.5, 2.9	620, 880, 1100, 1400, 1540

Technical Fact Sheet



Technical Data

Properties	UOM	Test method	Results
Thickness	UM		± 10% 1000 1500 2000 2500 2900
Grammage	GSM		± 10% 620 880 1100 1400 1540
Bending stiffness MD	mNm	DIN 53121	-15% 1050 ** **
Bending Stiffness CD	mNm	DIN 53121	485 ** **
Scott bond	J/m2		Min 100 120
Cobb 60. Gsm			Max 60 30