

Technical Fact Sheet



Stickler Coverall RP1001

Stickler Coverall is a white gloss paper produced with a black reverse for high opacity and blockout applications. Produced to present no show through, it has superior print performance.



Important Note

All statements, technical information and recommendation are based on tests believed to be reliable, the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection herewith.

Technical Fact Sheet



Backing

WG White glassine

WG white glassine backing allows high speed conversion and consistent dispensing on a wide range of equipment.

Properties	Result
Grammage	63 gsm
Opacity	> 45%
Caliper	56 microns

Technical Fact Sheet



Technical Data

NOTE: The substrate should be free of dust and lubricant before apply. Please use once unwrapped, if stock is to be returned to the storage shelf please ensure stock is wrapped and bagged to prevent surface dust and contamination. This product should be tested thoroughly under use condition to ensure it meets the requirements of the specific application.

Face Material:

Properties	Test Method	Result
Grammage	ISO 536	90 ± 5 g/m ²
Caliper	ISO 534	72 ± 5 microns

Adhesive:

RP1001-Type Extra Permanent (Hot Melt)

A rubber based hot-melt adhesive with high tack and adhesion, particularly on difficult and apolar substrates (PE,PP). Improved recipe for high speed converting.

Properties	Result
Composition	Rubber based Hot-Melt
Minimum Application Temperature	0°C
Service Temperature	-10 to +70 °C
Food contact	dry and moist direct
Tack FTM9 N/inch ²	16

Laminate:

Laminate Shelf Life 24 months stored at
23°C/50% RH
Typical Laminate Calliper 151 microns / 173gsm

Technical Fact Sheet



Ultimate adhesion FTM² N/inch 9

Technical Fact Sheet

