

Technical Fact Sheet



Stickler PP Silver TC AP901

Stickler PP TC 50 micron top coated silver polypropylene film produced with a brilliant gloss surface for crisp colour reproduction and optimum print results. Suitable for a number of print methods, from letterpress UV, screen, flexographic and offset printing.



Application Text

Stickler Silver PP can be used for a wide variety of applications where a demanding label substrate is required, from water, food & beverage, household, chemical and point of sale labels.

Technical Fact Sheet



Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Backing

WG White Glassine

1 side siliconised supercalendered white glassine

Properties Result

Grammage 62 gsm

Caliper 55 microns

Technical Fact Sheet



Technical Data

Face Material:

Technical Fact Sheet



Metallised silver – top coated polypropylene

Properties	Test Method	Result
Grammage	ISO 536	45 g/m ²
Caliper	ISO 534	50 microns

Technical Fact Sheet



Adhesive:

AP901 General Purpose Permanent

Permanent pure acrylic adhesive designed for films. Featuring high cohesion, good clarity and very good performance on non comparable substrates (PE,PP), approved for direct contact on the skin (plasters)

Properties	Test Method
Composition	Water based acrylic
Direct sunlight resistance	Excellent
Cohesion	High
Application temperature (min)	-5°C