

Technical Fact Sheet



Manter Tintoretto Black Pepper Ultra

Manter Tintoretto Black Pepper Ultra is a wet strength natural, pure cellulose paper, felt textured on both sides. Tintoretto Black Pepper Ultra is supplied with a unique co-extruded PE film designed to improve stability but also labelling and application performance.



Features

- FSC® certified (licensed code FSC® C010628)

Technical Fact Sheet



Application Text

Natural pure paper, recommended for wine label production where a slight felt finish embossing is preferred. Produced with wet-strength fibre composition for the performance in ice/water bucket, and areas where condensation is high.

Important Note

All statements, technical information and recommendation are based on tests believed to be reliable, the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection herewith.

Backing

CB80 Super calendared white glassine paper.

Backing paper designed for automatic label generation.

Technical Fact Sheet



Properties	Test Method	Result
Grammage	g/m^2	78 gsm
Caliper	Microns	67 microns

Technical Fact Sheet



Technical Data

Face Material:

Properties	Test Method	Result
Grammage	ISO 536	115 g/m ²
Caliper	ISO 534	150 microns
Opacity (Dry/wet)	%	90 / 77
Opacity variation	%	14
Tear strength (md/cd)	KN/m	6,2 / 2,7

Adhesive:

SH 6020 Plus

Permanent acrylic adhesive. Strong initial adhesion, high tack and good cohesion. Especially suitable for all-purpose applications on wet surfaces at low temperature. Excellent resistance to ice water.

Properties	Test Method	Result
Tack	FTM 9	> 12
Cohesion	(h) 1kg FTM 8	> 2
Application temperature (min)	°C	> +5 °C
Service temperature (max)	°C	> -10 °C
Service temperature	°C	75°C

Technical Fact Sheet

