

# Technical Fact Sheet



## Manter Eureka Ultra

Manter Eureka is a pure chlorine free (ECF) wet strength paper, produced with a subtle hammer embossed finish for a unique print result. Coated with ULTRA co-extrusion performance to ensure the highest water application performance.



---

### Features

- Pure chlorine free (ECF) wet strength paper
- Subtle hammer embossed finish
- Unique print result
- Coated with ULTRA co-extrusion performance
- Highest water application performance
- FSC® certified (licensed code FSC® C010628)

# Technical Fact Sheet



---

## Application Text

- Food and beverage
- Cosmetic
- Health care
- Wine labeling

---

## Printing Tips

Not suited to narrow curved applications

---

## Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

# Technical Fact Sheet



---

## Print Process

- Letterpress
- Flexo
- Screen
- Foil
- Offset-printing

---

## Backing

### CB80

Super calendared white glassine paper.

Backing paper designed for automatic label generation.

### Properties Result

Grammage 78 gsm

Caliper 67 microns

# *Technical Fact Sheet*



## **Technical Data**

**Face Material:**

# Technical Fact Sheet



## Properties Test Method Result

Grammage g/m<sup>2</sup>      100 g/m<sup>2</sup>

Caliper      Micron      130

## Adhesive:

### SH 6020 Plus - Permanent Acrylic adhesive

Permanent acrylic adhesive. Strong initial adhesion, high tack and good cohesion. Especially suitable for all-purpose applications on wet surfaces at low temperature. Excellent resistance to ice water.

Properties	Test Method Results
------------	---------------------

Tack	(N) FTM9      > 12
------	--------------------

Cohesion	N/1kg FTM-8 > 2
----------	-----------------