

# *Technical Fact Sheet*



## **dtec Backlit PET Matt**

dtec Backlit PET Matt is a translucent white Polyester (PET) film for all types of backlit applications. Printable surface is on the outside of the roll.



---

### **Important Note**

All values presented in this data sheet provide the general characteristics of the product. It is the responsibility of the customer and/or end user to determine that the product is fit for the specific application it is to be used for.

# Technical Fact Sheet



---

## Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of relative humidity. Do not expose to direct sunlight. The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

---

## Print Process

### Ink Compatibility:

- Solvent
- Eco Solvent
- UV Curable Inkjet
- Latex

# *Technical Fact Sheet*



## Technical Data

# Technical Fact Sheet



Properties	Unit	Result
Weight	GSM	300
Thickness	Um	210
Haze	%	2
Heat Shrinkage	%	0.5
Tensile Strength Kg/mm <sup>2</sup> 18 (ASTM D 882)		
Elongation	%	185 (ASTM D 882)

# Technical Fact Sheet



**Base Material:** Polyester (PET)

**Colour:** White translucent print surface

**Outdoor  
Life:**

General life time refers to the durability of the unprinted material when subject to vertical exposure in temperate, non-extreme conditions. Actual performance life will depend on media and surface preparation and exposure conditions. For example the direction and angle of the sign; in areas of long, high temperature exposure; in areas of high pollution or high altitudes, outdoor performance will be decreased.