

Technical Fact Sheet



Triplex Fotocopy

Triplex Fotocopy is of triplex construction, also referred to as piggyback. First layer: white, smooth natural paper, wood free.



Application Text

Typical applications include double layer labels for industrial uses and variable information printing.

Technical Fact Sheet



Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Print Process

Suitable for various printing systems and laser printers. Testing for suitability between media, printers and inks is always recommended prior to use

Backing

Glassine Paper

Properties	Result
Colour and Finish	White

Technical Fact Sheet



Grammage 62g/m² PP-032 – ISO 536

Caliper 55 um ISO 534

Technical Fact Sheet



Technical Data

Note: The material must be stored at temperature of 22 °C +/-2°C and 50% +/-5% of relative humidity. Do not expose to direct sun light. The area must be dry and clean, please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

Face Material:

Properties	Test Method	Result
Grammage	ISO 536	68 g/m ²
Caliper	ISO 534	77 microns

Adhesive: AP 904 - Permanent, water based acrylic adhesive for general purpose

Properties	Result
Composition	Acrylic permanent
Minimum Application Temperature	+ 5°C
Service Temperature	-20 °C/+100 °C
Shear	Medium
Tack	13 N/inch ²
Ultimate adhesion	10 N/inch ²

Technical Fact Sheet

