

# Technical Fact Sheet



## Stickler TT Matt RP1011

Stickler TT Matt RP1011 is a matt coated paper designed for premium print reproduction and thermal transfer applications.



---

### Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

# Technical Fact Sheet



## Backing

WG62 One sided siliconised glassine liner

### Properties Test Method Result

Grammage ISO 536 62 gsm

Thickness ISO 534 55 microns

# *Technical Fact Sheet*



## **Technical Data**

**Face Material:**

# Technical Fact Sheet



## Properties Test Method Result

Grammage ISO 536 73 g/m<sup>2</sup>

Thickness ISO 534 76 µm

# Technical Fact Sheet



**Adhesive: RP1011 Rubber Permanent**

Rubber based permanent adhesive with high grammage and high tack and adhesion on difficult and non-comparable (PE, PP) substrates.

<b>Properties</b>	<b>Test Method</b>
Composition	Rubber permanent
Shear	Very high
Application temperature °C	0 °C (minimum)
Service temperature °C	-10 to +70 °C
Tack FTM 9	19N/Inch <sup>2</sup>