

Technical Fact Sheet



Ferro Film

Ferro Film Is a white matt PP Steel film, compatible for (eco) solvent, UV curable printing. Working as magnetism principle on magnets, easy to apply, remove and change, without residue.



Application Text

- Magnetic
- POS Displays
- Promotional graphics
- Wallgraphics

Technical Fact Sheet



Important Note

All values presented in this data sheet provide the general characteristics of the product. It is the responsibility of the customer and/or end user to determine that the product is fit for the specific application it is to be used for.

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of relative humidity. Do not expose to direct sunlight. The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

Print Process

Printable UV inkjet and latex

Technical Fact Sheet



Technical Data

Technical Fact Sheet



Total Thickness	250m (±25)
Weight	320g/M2 (±30)
Whiteness	[80,90]
Gloss 60°	[3, 8]
Opacity	100%
Water Resistance	Medium – high

Technical Fact Sheet



- Not recommended to use in cold area (outdoor temperature is below 0 °c)
- Not recommended to use on big graphics with 1.5M length or more.
- Excess UV Ink piling should be avoided. Soft UV ink is recommended.