

Technical Fact Sheet



Stickler Foto Copy 70 Rem 80

Stickler Foto copy is a surface sized woodfree paper, printable with traditional systems and laser.



Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Technical Fact Sheet



Storage

The material must be stored at temperature of 22 °C +/-2°C and 50% +/-5% of relative humidity. Do not expose to direct sun light. The area must be dry and clean, please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

Print Process

Labels on sheet for photocopy and laser printers

Backing

1 sided clay-coated kraft backing for good lay flat properties

Properties Result

Grammage 55 gsm

Caliper 58 microns

Technical Fact Sheet



Technical Fact Sheet



Technical Data

Face Material:

Technical Fact Sheet



Properties Test Method Result

Grammage ISO 536 $70 \pm 5 \text{ g/m}^2$

Caliper ISO 534 $93 \pm 5 \text{ microns}$

Adhesive: **FR20 - Removable**

A general purpose removable, acrylic adhesive

Properties

Result

Composition Acrylic removable

Minimum Application Temperature + 5°C