

Technical Fact Sheet



Bauhaus 39 Proof 260

Bauhaus 39 Proof is FOGRA certified to meet ISO12647-7 standard. Fogra 39 semi matt micro-porous resin coated proofing paper. High colour fidelity with a unique semi matt finish and wide colour gamut.



Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Technical Fact Sheet



Print Process

Compatibility: Aqueous (Dye & Pigment), Indigo & Latex.

Technical Fact Sheet



Technical Data

Technical Fact Sheet



	Result	Unit	Standard
Weight	255 ± 10	g/m ²	ISO 536
Paper thickness	270 ± 12	µm	ISO 534
Gloss 75 degrees	52 ± 5	%	ISO 8254
Brightness	91 ± 3	%	ISO 2470
Opacity	96 ± 3	%	ISO 2471
Stiffness MD	2.3 ± 0.8	mN -m	ISO 2493

Technical Fact Sheet



Stiffness CD	1.3 ± 0.5	mN-m	ISO 2493
L*	96.5 ± 1.5		D50/2
a*	0.0 ± 0.8		
b*	-2.5 ± 0.8		