

Technical Fact Sheet



Stickler Coated 80 H260

Stickler Coated 80 H260 is a white clay coated paper produced with medium gloss levels for quality 4 colour print reproduction. Designed for high speed label production. Stickler Coated 80 is suitable for all print methods.



Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Technical Fact Sheet



Backing

WG 62 - One sided siliconised glassine liner.

Properties	Result
Grammage	60 gsm
Caliper	55 microns

Technical Fact Sheet



Technical Data

Face Material:

Properties	Test Method	Result	Adhesive: H260 - Rubber Permanent		
Grammage	ISO 536	80 g/m ²	A rubber base permanent adhesive with high grammage and high tack and adhesion on difficult and apolar (PE, PP) substrates.		
Caliper	ISO 534	69 microns	Properties	Result	Laminate: Laminate shelf life
			Composition	Rubber permanent	- 12 months stored at 20°C/50%RH
			Shear	Very High	Typical laminate caliper - 138 microns +/- 6 um (ASTM D374-88)
			Application temperature (min) °C	+0°C to +40°C	Total weight - 159 +/- 6 (RIT.PP-032)
			Service temperature °C	-25°C to +80°C	
			Tack FTM 9	20 N/Inch	
			Ultimate adhesion FTM 2	12 N/Inch	

Technical Fact Sheet



Technical Fact Sheet

