

Technical Fact Sheet



Stickler Coated 80 AJ900

Stickler Coated 80 AJ900 is a white clay coated paper produced with medium gloss levels for quality 4 colour print reproduction. Designed for high speed label production. Stickler Coated 80 is suitable for all print methods.



Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Technical Fact Sheet



Backing

White Glassine – WG 1 side siliconised, super-calendered white glassine

Properties	Result
Grammage	62 gsm
Caliper	56 microns
Transparency (%)	> 45%

Technical Fact Sheet



Technical Data

Face Material:

Technical Fact Sheet



Properties Test Method Result

Grammage ISO 536 80 g/m²

Caliper ISO 534 69 microns

Technical Fact Sheet



Adhesive: AJ900 Permanent Acrylic adhesive

Good adhesion on a wide variety of materials including apolar surfaces

Properties	Result
Composition	Acrylic permanent
Shear	Medium
Application temperature (min) °C	+5°C
Service temperature °C	-15°C to +70°C
Tack FTM 9	13 N/Inch