

Technical Fact Sheet



Pacesetter Self Adhesive Matt Coated HB

Pacesetter Self Adhesive Matt Coated HB is a PE laminated white paper suitable for promotional and general labelling.



Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Technical Fact Sheet



Technical Data

Technical Fact Sheet



ITEM			SPECIFICATION	METHOD
Self adhesive label	MCP(Y)-S-WP(12A)	Basis weight (g/m ²)	239.0 ± 10.0	ISO 536
		Thickness (µm)	258 ± 10	ISO 534
Facestock	Matt Coated Paper	Basis weight (g/m ²)	82.0 ± 5.0	ISO 536
		Thickness (µm)	72 ± 5	ISO 534
Adhesive	Strong glue	Peel adhesion (N/25mm)	> 8.8	
		Initial tack (N/25mm)	> 7.8	FTM 1 - Glass
		Cohesion (min)	> 900	FTM 9 - Glass
		Minimum application temp. (°C)	5	FTM 8
		Service temp. (°C)	-20 to 80	
		Product Validity *	1 year	
Liner	Uncoated White paper with PE resin extrusion	Basis weight (g/m ²)	135.0 ± 5.0	ISO 536
		Thickness (µm)	170 ± 5	ISO 534

Technical Fact Sheet



* Product Validity : The properly glue adhesion on our "Oji Label" self adhesive label can be maintain adhesive strength at least 1 year when stored under 23 °C and 50% RH with the original packaging.

Caution and Suggestion

The substrate should be free of dust and lubricant before apply.

Please use once unwrapped, if there are remains it must to be wrapped by original wrapper.

Do not expose to direct sunlight or heat sources.

This product should be tested thoroughly under use condition to ensure it meet the requirement of the specific application.

Technical Fact Sheet

