

# Technical Fact Sheet



## Stickler PP Clear TC H160

Stickler PP TC 50 Clear Gloss is a clear polypropylene top coated film designed for ultimate label application conformation on many difficult and contoured surfaces. Supplied with good clarity for optimum print results and label performance giving the stock a cloud free/high resolution finish.



---

### Application Text

The products are suitable for a wide range of promotional and industrial label applications.. It's suitable for flat or simple curve substrates.E.g: glass, steel, smooth carton, daily using...

# Technical Fact Sheet



---

## Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

---

## Backing

1 side siliconised supercalendered white glassine

Properties	Result
------------	--------

Grammage	60 gsm
----------	--------

Caliper	55 microns
---------	------------

Transparency	>40%
--------------	------

# *Technical Fact Sheet*



## **Technical Data**

**Face Material:**

# Technical Fact Sheet



Properties	Test Method	Result
Grammage	ISO 536	38 g/m <sup>2</sup>
Caliper	ISO 534	40 microns
UV exposure Depending on ink coverage: 6 month		

# Technical Fact Sheet



## **Adhesive: H160 - Rubber Based Extra Permanent**

A rubber based extra Permanent adhesive designed for films, offering excellent high tack and adhesion on particularly difficult rough and apolar substrates (PE,PP)

Properties	Test Method
Composition	Rubber based extra permanent
Direct sunlight resistance	Excellent
Cohesion	Very high
Application temperature (min)	-0°C to 40°C
Service Temperature	-25°C + 80°C