

Technical Fact Sheet



Rocal 3yr SAV GLOSS

Rocal 3yr SAV GLOSS is a three-year rated gloss self-adhesive vinyl for everyday signage and promotional graphics. It provides a bright printable gloss finish for short- to mid-term indoor and outdoor applications. Suitable for signage, display graphics and wide-format print applications.



Features

Product Information Suggestion

Composition:	Calandered PVC film, adhesive & release paper
Main Applications:	Short term permanent mounted graphics
Features:	Controlled, reliable print formulation & shrinkage, stay-flat liner
Benefits:	Reliable printing, high durability & flatness, visually appealing

Technical Fact Sheet



Formulation: Plasticised Monomeric Vinyl
Storage Conditions: 5~40°C & 35~75% RH in the original packaging
Shelf Life: 1 year from date of manufacture
Release Liner: Thick kraft paper with double side PE coated
Adhesive Type: Clear permanent solvent based acrylic
Remarks: Total weight including liner & adhesive 320gsm

Environmental Credentials

Eco Response Testing Method

Heavy Metal Free No

Recyclable No

Safety Compliance RoHs Certified

Printing Tips

Printing and Laminating Suggestion

Printable Sides: One, wound facing outside of roll

Technical Fact Sheet



Ink Suitability: UV Cured inks (Offset, Screen & Inkjet) Solvent & Latex
Laminating: Cold lamination with minimum tension, ROLAM 3 yrs LAM suggested

Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Storage

Durability	Testing Method
Indoor	6 years
Outdoor	3 years
Clean Removability	

Technical Fact Sheet



Size Availability

Stock Availability	Suggestion
---------------------------	-------------------

Roll Widths (mm):	1370 & 1524mm
-------------------	---------------

Roll Lengths (mtrs):	50m (250 & 500m by request)
----------------------	-----------------------------

Standard Core:	3 inch paper core
----------------	-------------------

Technical Fact Sheet



Technical Data

[Product Safety Datasheet](#)

Basic Physical Data

Suggestion

Thickness:	300 micron \pm 20 micron
Weight:	320 grams per m ² \pm 20 grams
Gloss Level:	80 \uparrow Degree/60°Angle
Matt Level:	6 \pm 4 Degree/60°Angle
Satin Level:	
Clear Clarity	No

Thermal Data

Suggestion

Heat Resistance:	80°C
Cold Resistance:	-30°C
Shrinkage:	0.5 \downarrow % (80°Cx48hrs)

Physical Characteristics Suggestion