

Technical Fact Sheet



Ace Kraft Screenboard

Ace Kraft is an uncoated display board with a natural, kraft surface on both sides that is ideally suited for large format digital printing. Premium, kraft twin sided rigid & dimensional stable display board. FSC Mix Certified.



Features

- Natural kraft look & feel
- Clean pure centre
- Outstanding stay flat properties
- FSC® Certified (licensed code FSC® C010628)
- Fully Recyclable
- Biodegradable

Technical Fact Sheet



Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Application Text

- Hanging signage
- POS displays
- Aisle fins
- Header cards
- Category signage
- Promotional signage
- Shop window promotions
- Exhibition stands
- Mounting

Technical Fact Sheet



Environmental Credentials

Spicers Key Icons

[Download Spicer's icons](#)

Storage

Print Process

Technical Fact Sheet



PRINTING

- Offset printing
- screen printing
- large format digital printing

CONVERSION

- embossing
- foil and film lamination
- varnishing
- die cutting
- creasing
- perforating
- cutting and scoring

Technical Fact Sheet



Technical Data

SUBSTANCE	THICKNESS			BENDING RESISTANCE		BENDING MOMENT	
	mm	µm	pt	L&W 15° mN	MD	CD	Taber 15° mNm
875	1.5	1500	59	*	*	*	*
1070	2	2000	79	*	*	*	*
1575	3	3000	118	*	*	*	*

*values cannot be measured

Tolerances / Testing Standards

Grammage (DIN ISO 536)	±10%
Thickness (DIN ISO 534)	±10%
Bending stiffness (ISO 5629)	±20%
Brightness C/2° (ISO 2470)	
Surface smoothness Bendtsen (ISO 8791-2)	

Printing Surface Properties

ISO Brightness	
CIE Whiteness D65/10° (ISO 11475)	
Surface smoothness (Bendtsen)	1500 ml/min
Gloss 75° (ISO 8254-1)	