

# *Technical Fact Sheet*



## **Stickler PPTC Clear AS500 WG**



---

### **Application Text**

The products are suitable for a wide range of promotional and industrial label applications.. It's suitable for flat or simple curve substrates. Ex: glass, steel, smooth carton, daily using...

# Technical Fact Sheet



---

## Printing Tips

Designed to be converted by flexographic, offset letter press, gravure and silk screen. However, testing is recommended prior to ink selection.

---

## Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

---

## Storage

1 year under 20°C and 50% humidity. Please avoid direct sunlight and wet environment. Used within 6 months after printing to achieve best quality.

---

## Size Availability

# *Technical Fact Sheet*



Width: 1530mm Roll length: 500m-3000m

# *Technical Fact Sheet*



## **Technical Data**

### **Face Material: Transparent PP**

Top coated clear pp

TYPICAL SPECIFICATIONS:

# Technical Fact Sheet



Weight: 35 +/- 2 m2/kg MTM 1  
Caliper: 50 +/- 1 um MTM 1  
Tensile strength: 170 N/mm2 DIN 53455  
Tensile strength CD: 200 N/mm2 DIN 53455  
Glossness >= 85 % ASTM D245745°

## ADHESIVE: Permanent AS500

Excellent permanent pressure sensitive adhesive

Weight:	20 +/- 2	g/m2
Tack:	18	N FTM 9
Shear:	15	h FTM 8
Peel adhes. 180o	0.35	kN/m FTM 1
Appl. temp. min	0	oC
Service temp.:	-20 ~ 80	oC
Turn up:	No	

Character: Permanent Acrylic base adhesive. Stable and