

Technical Fact Sheet



Stickler PP68Cav AS500 (R)



Application Text

Recommended for FMCG, beverage, water, cosmetic and healthcare labels

Technical Fact Sheet



Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Backing

WG White Glassine

1 side siliconised supercalendered white glassine

Properties	Result
------------	--------

Grammage	62 gsm
----------	--------

Caliper	55 microns
---------	------------

Transparency	49%
--------------	-----

Technical Fact Sheet



Technical Data

Face Material:

Technical Fact Sheet



Properties	Test Method	Result
Grammage	ISO 536	53 g/m ²
Caliper	ISO 534	68 microns
UV exposure Depending on ink coverage: 6 month		

Technical Fact Sheet



Adhesive:

AS 500 General Purpose Permanent Permanent pure acrylic adhesive designed for films. Featuring high cohesion, good clarity and very good performance on non comparable substrates (PE,PP), approved for direct contact on the skin (plasters)

Properties	Test Method
Composition	Water based acrylic
Direct sunlight resistance	Excellent
Cohesion	High
Application temperature (min)	0°C
Service Temperature	-20°C + 80°C