

Technical Fact Sheet



Stickler PP Thml H160 WG



Application Text

The products are suitable for a wide range of promotional and industrial label applications. It is suitable for flat or simple curve substrates. E.g: glass, steel, smooth carton

Technical Fact Sheet



Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Backing

1 side siliconised supercalendered white glassine

Properties	Result
------------	--------

Grammage	60 gsm
----------	--------

Caliper	55 microns
---------	------------

Transparency	>49%
--------------	------

Technical Fact Sheet



Technical Data

Face Material:

Technical Fact Sheet



Properties Test Method Result

Grammage ISO 536 67 g/m²

Caliper ISO 534 80 microns

Brightness ISO 2470 80%

Technical Fact Sheet



Adhesive: H160 - Rubber Based Extra Permanent

A rubber based extra Permanent adhesive designed for films, offering excellent high tack and adhesion on particularly difficult rough and apolar substrates (PE,PP)

Properties	Test Method
Composition	Rubber based extra permanent
Direct sunlight resistance	Excellent
Cohesion	Very high
Application temperature (min)	-0°C to 40°C
Service Temperature	-25°C + 80°C