

# Technical Fact Sheet



## Precision Laser NS 70-120gsm PEFC(S)

Precision Laser NS is the go-to choice for those who demand both quality and affordability. This extraordinary all-purpose offset paper boasts superior bulk and opacity characteristics, with exceptional print results that will leave a lasting impression.



---

### Features

- PEFC certified
- Economically priced
- Excellent runnability and bulk
- Laser guaranteed
- ISO 14001 environmental certification
- Available in 70, 80, 90, 100, 110 and 120 gsm

# *Technical Fact Sheet*



---

## Spicers Key Icons

[Download Spicer's icons](#)

---

## Application Text

- Annual reports
- Brochures
- Catalogues
- Certificates
- Corporate Identity
- Desk pads
- Direct mail
- Flyers
- Posters
- Stationery

# Technical Fact Sheet



---

## Printing Tips

- Designed for offset applications
- Suitable for commercial four colour reproduction printing
- Under Colour Removal (UCR) Recommended
- Precision is Laser Guaranteed to 120gsm for up to 100 pages per minute

---

## Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

---

## Print Process

- Creasing
- Die cutting
- Embossing

# Technical Fact Sheet



- Foiling
- Folding
- Inkjet
- Laminating
- Laser
- Scoring

---

## Size Availability

Option	GSM
Text	70, 80, 90, 100, 110, 120

# Technical Fact Sheet



## Technical Data

Parameter	Unit						
Grammage	g/m <sup>2</sup>	70	80	90	100	110	120
Thickness	μm	91 +/- 2	104 +/- 2	115 +/- 2	128 +/- 2	145 +/- 2	158 +/- 2
Opacity	%	>93					
Smoothness	W sec/10ml T 479 OM - 09	15.0 - 35.0					
	F sec/10ml T 479 OM - 09	15.0 - 35.0					