

Technical Fact Sheet



Precision Laser NS 70-120gsm PEFC(S)

Precision Laser NS 70–120gsm PEFC is a PEFC-certified uncoated paper range for laser printing across a range of non-standard weights. Offering excellent opacity, whiteness, and smooth surface for reliable laser performance, it is ideal for premium documents, stationery, forms, and eco-conscious laser print applications.



Features

- PEFC certified
- Economically priced
- Excellent runnability and bulk
- Laser guaranteed
- ISO 14001 environmental certification
- Available in 70, 80, 90, 100, 110 and 120 gsm

Technical Fact Sheet



Spicers Key Icons

[Download Spicer's icons](#)

Application Text

- Annual reports
- Brochures
- Catalogues
- Certificates
- Corporate Identity
- Desk pads
- Direct mail
- Flyers
- Posters
- Stationery

Technical Fact Sheet



Printing Tips

- Designed for offset applications
- Suitable for commercial four colour reproduction printing
- Under Colour Removal (UCR) Recommended
- Precision is Laser Guaranteed to 120gsm for up to 100 pages per minute

Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Print Process

- Creasing
- Die cutting
- Embossing

Technical Fact Sheet



- Foiling
- Folding
- Inkjet
- Laminating
- Laser
- Scoring

Size Availability

Option	GSM
Text	70, 80, 90, 100, 110, 120

Technical Fact Sheet



Technical Data

Parameter	Unit						
Grammage	g/m ²	70	80	90	100	110	120
Thickness	μm	91 +/- 2	104 +/- 2	115 +/- 2	128 +/- 2	145 +/- 2	158 +/- 2
Opacity	%	>93					
Smoothness	W sec/10ml T 479 OM - 09	15.0 - 35.0					
	F sec/10ml T 479 OM - 09	15.0 - 35.0					