

Technical Fact Sheet



GF SAV 5 yr 201 203

General Formulations 201 and 203 are 3.4 mil polymeric white calendered vinyls, with a clear permanent acrylic pressure sensitive adhesive. Features a 90# layflat liner. The clear adhesive creates a permanent bond to a variety of common substrates used in graphics applications. The 90# liner provides excellent layflat qualities in a variety of ambient conditions along with ease of application of large format graphics. Suitable for solvent, eco-solvent, latex and UV curable inks.



Features

- 99% Opacity with Excellent Hiding Power
- Resistant to Chemicals & Cleaning Agents
- Designed for More Demanding & Durable, Long-Term Applications
- Lower Initial Tack for Better Repositionability
- Air Egress Option (OPAE) for Quick, Easy, Bubble-Free Applications

Technical Fact Sheet



Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Printing Tips

Please refer to [GF ICC Print Profile](#)

Print Process

Solvent

Eco-Solvent

Latex

UV Curable

Technical Fact Sheet



Screen

Offset (UV Curable)

Application Text

General Signage

POP & Indoor Signage

Technical Fact Sheet



Technical Data

Please refer to [GF Technical Data](#)

Technical Fact Sheet

