

Technical Fact Sheet



RC Kraft

RC Kraft is a multi layer coated kraft board with unbleached reverse side. The boards great rigidity and strength, combined with excellent printing surface and exceptional freezer performance makes it a world class choice for a wide range of packaging applications.



Features

- FSC® Certified (licensed code FSC® C010628)
- Great rigidity
- Excellent Runnability
- Yield advantages
- Smooth double coated top surface
- Suitable for freezer and fridge applications

Technical Fact Sheet



- Direct contact with dry, moist, acidic and fatty foodstuffs
-

Application Text

- Frozen foods
 - Food packaging
 - Beverage packaging
 - Chocolate and confectionery packaging
 - Industrial and logistics - Heavy parts packaging
 - Electronics
 - Pharmaceutical
-

Printing Tips

- Sheet fed-offset
- Flexographic
- Digital Printing
- Screen printing
- Folding/creasing/scoring
- Die-cutting

Technical Fact Sheet



- Embossing
- Foiling
- Gluing

Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Technical Fact Sheet



Technical Data

Technical Fact Sheet



Grammage GSM	Thickness UMS	Bending Stiffness CD mNm (Tappi 489)	Bending Stiffness MD mNm (Tappi 489)	Value Cobb	ISO Brightness TOP %		Moisture	Smoothness PPS10 Top μm
				TOP	REVERSE			
245	400	6.4	13.3	<-45	<-80	81+/-2	6.5-9.5	1.0+0.5
265	457	9.3	19.3	<-45	<-80	81+/-2	6.5-9.5	1.0+0.5
285	508	11.8	24.5	<-45	<-80	81+/-2	6.5-9.5	1.0+0.5
310	559	14.9	31.3	<-45	<-80	81+/-2	6.5-9.5	1.0+0.5
330	610	18.3	38.3	<-45	<-80	81+/-2	6.5-9.5	1.0+0.5
345	660	20.6	43.9	<-45	<-80	81+/-2	6.5-9.5	1.0+0.5