

Technical Fact Sheet



Pacesetter Self Adhesive Vellum

Pacesetter Self Adhesive Vellum is a cost effective permanent acrylic sheet that is well suited for promotional and general labelling with no compromise in quality. Offering a perfect combination of initial tack, adhesive strength and outstanding adhesion to most substrates, Pacesetter can help meet any specific requirements. Available in Permanent and Removable adhesive and also heavy backing.



Features

- Acrylic permanent, removable, freezer and wine permanent adhesives
- Economical
- Excellent printability and performance
- Sheet fed printer driven – trouble free printing, multiple applications and embellishments
- Uncoated white woodfree label paper
- Digital version Dry Toner compatible and available in permanent only

Technical Fact Sheet



- Split runs 50mm apart parallel with grain direction

Spicers Key Icons

[Download Spicer's icons](#)

Application Text

- High impact labels and signage
- Large window stickers
- POP advertising
- Promotional and general labelling
- Promotional labels

Printing Tips

Technical Fact Sheet



UCP(N) is preferred for general application in all printing technology and also possible for laser printing application with prior test approved before real application.

The substrate should be free of dust and lubricant before applying. Please use once unwrapped, if there are remains they need to be wrapped by an OLT wrapper. This product should be tested thoroughly under use condition to ensure it meet the requirement of the specific application.

We always recommend that the sheet is test and trialled before commencing a print job. This is to determine that the sheet is suitable for the particular machine and the particular print job.

Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Storage

1 year shelf life when stored at 23 oC, 50 % RH, in the original packaging.

Technical Fact Sheet



Print Process

- Letterpress
- Offset
- Flexography
- Silkscreen
- Hot Foil Stamping
- UV Varnish

Face Material

Uncoated white woodfree printing label paper which excellent properties with good smoothness for outstanding print quality requirement especially for non- impact printer.

Backing

Uncoated white kraft paper with high quality of clay coated to made good dimensional stability, density and have good lay flat sheet such made even and stable paper thickness. Better paper strength and excellent for die cutting.

Technical Fact Sheet



Backing technical data:

Basis weight (g/m²) 82 ISO 536

Thickness(μm) 87 ISO 534

Size Availability

Options	Type	GSM
White	Solid, Split	70

Technical Data

—