

# Technical Fact Sheet



## Rocal POPDOT

Rocal POPDOT is up to 3-year monomeric vinyl with a dot pattern, clear, removable adhesive. Available in matt white, gloss white and Clear finishes. Quick and easy, bubble free installation with no need for tools or wet application. Clean removal up to 1 year from installation. Recommended for short term indoor applications on windows, walls & other internal flat surfaces. For clean, flat, smooth and lightly textured surfaces (indoors).



---

### Features

- Quick & Easy, bubble free installation with no need for tools or wet application
- Clean removal up to 1 year from installation
- Recommended for short-term indoor applications on windows, walls & other internal flat surfaces.

# Technical Fact Sheet



---

## Application Text

- Window graphics
- Exhibition graphics
- POS
- Promotional graphics
- Wall graphics

---

## Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

---

## Storage

# *Technical Fact Sheet*



The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of relative humidity. Do not expose to direct sunlight. The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

# Technical Fact Sheet



## Technical Data

### FACE MATERIAL

Type	Calendared monomeric PVC film
Colour/Finish	White Matt / White Gloss / Clear
Thickness	100 $\mu$ $\pm$ 10% (without liner and adhesive)
Outdoor Life Expectancy	nil

### ADHESIVE

Colour & Type	Clear, Dot pattern, poly-acrylate, removable
Thickness	13 $\mu$ $\pm$ 2 micron
Application Temp	>50 °C
Service Temp.	-15°C to +60°C

### RELEASE BACKING

# Technical Fact Sheet



Type	One side siliconized clay coated kraft
Colour/Finish	White
Weight	135 gsm $\pm$ 10%