

Technical Fact Sheet



Stickler PP68 CAV AP901 PET

Stickler PP68 CAV AP901 PET is a top-coated cavitated polypropylene label film with AP901 adhesive and PET liner for improved press runnability and dimensional stability. Compatible with inkjet, offset, and digital processes, it is ideal for product labels, cosmetics, and high-speed commercial labelling.



Application Text

Recommended for FMCG, beverage, water, cosmetic and healthcare labels

Technical Fact Sheet



Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Backing

PET23

A one sided siliconised polyester liner for maximum strength on application and ideal glue coverage allowing no adhesive lines or distortion.

Properties Result

Weight 32 g/m² ± 10% PP-032-ISO 536

Thickness 23 um ± 10% ISO 534

Technical Fact Sheet



Technical Data

Face Material:

Technical Fact Sheet



Properties	Test Method	Result
Grammage	ISO 536	53 g/m ²
Caliper	ISO 534	68 microns
UV exposure	Depending on ink coverage: 6 month	

Technical Fact Sheet



Adhesive: AP901 General Purpose Permanent

Permanent pure acrylic adhesive designed for films. Featuring high cohesion, good clarity and very good performance on apolar substrates (PE,PP), approved for direct contact on the skin (plasters)

Properties

Test Method

Composition

Water based acrylic

Direct sunlight resistance

Excellent

Cohesion

High

Application temperature (min) -5°C