

# Technical Fact Sheet



## Yupo Octopus XAD1069 Reels

A synthetic paper that adheres to FLAT, SMOOTH, CLEAN & DRY surfaces such as glass, acrylic, PVC, aluminium, polypropylene & coated paper. Yupo® Octopus uses a new technology called 'micro-suction' on the bottom side. No glue is used, so there is no glue residue left on the material when it is removed. No magnet or static electricity is used, so it may be used on electrical devices such as TV's and PC's without any negative effects. Removable and reusable. The suction side may be cleaned with a wet cloth if dust does begin to build up. UV stabilised with an indefinite indoor lifespan. Temperature Tolerance -20 to +60 degrees Celsius. Recommended for INDOOR APPLICATIONS ONLY.



---

### Features

- Premium film that offers superior print and removability for multiple POS and retail applications
- Easy to apply, remove and reapply
- Thicker, more rigid liner making the product more stable when printing and easier to cut

# Technical Fact Sheet



---

## Application Text

- Window graphics
- Exhibition graphics
- POS
- Promotional graphics

---

## Printing Tips

### Printing Compatibility

- UV Screen
- UV Curable Inkjet
- UV Offset Printable

---

### Tips for Applying

- Ensure the surface that Yupo Octopus is being applied to is:
- Clean & Dry– wipe away all dust and moisture!
- The smoother the surface the better adhesion Octopus will have

---

### For Small Decals

# Technical Fact Sheet



- Remove the backing sheet
  - Grip on the ends of the printed sheet
  - Apply Yupo Clear to the surface from the centre of the sheet
  - Let go of the edges, and the sheet will naturally bond with the surface
  - Remove any air bubbles with an applicator – to minimise damage be sure to use the fabric covered edge
- 

## For Large Decals

- Remove the backing sheet
  - Apply a small amount of water to the printed sheet (on the side that will be applied to the surface)
  - Grip on the ends of the sheet
  - Apply Yupo Clear to the surface from the centre of the sheet
  - Let go of the edges, and the sheet will naturally bond with the surface
  - Remove the layer of water with an applicator – to minimise damage be sure to use the fabric covered edge
- 

## Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

# *Technical Fact Sheet*



---

## **Size Availability**

Finish - Satin

Width - 1270

Length - 20 & 100 LM

# *Technical Fact Sheet*



## Technical Data

Base Material	XAD1069
Nominal Weight	166 gsm
Thickness	210 µm