

Technical Fact Sheet



Yupo Octopus XAD1068 Clear

Yupo Octopus XAD1068 Clear adheres to any clean, dry and smooth surface by low-tack resin. Removable and reusable. Easy to apply and remove. Optically clear. No residue left behind when removed. If dirty simply clean with a damp cloth and reapply. Suitable for use in temperatures from 0°C to + 100 °C. INDOOR APPLICATIONS ONLY.



Features

- Easy to apply and is removable and reusable
- Adheres to any clean, dry and smooth surface by way of low-tack resin
- Perfect for window graphics and multiple POS & retail applications

Technical Fact Sheet



Application Text

- Window graphics
- Exhibition graphics
- POS
- Promotional graphics

Printing Tips

Printing Compatibility

- UV Screen
- UV Curable Inkjet
- UV Offset Printable

Tips for Applying

- Ensure the surface that Yupo Octopus is being applied to is:
- Clean & Dry– wipe away all dust and moisture!
- The smoother the surface the better adhesion Octopus will have

For Small Decals

Technical Fact Sheet



- Remove the backing sheet
 - Grip on the ends of the printed sheet
 - Apply Yupo Clear to the surface from the centre of the sheet
 - Let go of the edges, and the sheet will naturally bond with the surface
 - Remove any air bubbles with an applicator – to minimise damage be sure to use the fabric covered edge
-

For Large Decals

- Remove the backing sheet
 - Apply a small amount of water to the printed sheet (on the side that will be applied to the surface)
 - Grip on the ends of the sheet
 - Apply Yupo Clear to the surface from the centre of the sheet
 - Let go of the edges, and the sheet will naturally bond with the surface
 - Remove the layer of water with an applicator – to minimise damage be sure to use the fabric covered edge
-

Important Note

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

Technical Fact Sheet



Technical Data

Base Material	Polyester
Nominal Weight	235 gsm
Thickness	178 μm (face film & low-tack resin is 128 μm)

Technical Fact Sheet

