

Technical Fact Sheet



Digitac Floortac Indoor SAV

Digitac Floortac Indoor SAV is a matt white, hexagonal textured monomeric vinyl with a grey, airflow, removable adhesive. Suitable for indoor hard, flat surfaces (not recommended for carpet). Recommended for short term indoor campaigns and promotional applications. This product has a R10 non slip rating & requires no over laminate.



Features

- No laminate required
- Anti-slip certificate: R 10
- Suitable for Solvent, Eco-solvent, Latex and UV-Inkjet printing
- Suitable for indoor hard, flat surfaces (not recommended for carpet)

Technical Fact Sheet



Application Text

- Floor Graphics

Important Note

All values presented in this data sheet provide the general characteristics of the product. It is the responsibility of the customer and/or end user to determine that the product is fit for the specific application it is to be used for. All values presented in this data sheet provide the general characteristics of the product. It is the responsibility of the customer and/or end user to determine that the product is fit for the specific application it is to be used for.

Technical Fact Sheet



Technical Data

Technical Fact Sheet



FACE MATERIAL	
Type	Calendared monomeric PVC Film
Colour/Finish	White/Hexagonal textured matt
Thickness	150 μ \pm 10% (without liner and adhesive)
Dimensional stability MD	0.5mm-Finat 14
Dimensional stability CD	0.5mm-Finat 14
Dimensional Stability	0.5mm max
Anti-slip certificate	R 11
Indoor Life	Up to 1 year (depending on type and volume of traffic)

Technical Fact Sheet



ADHESIVE	
Colour & Type	Water based, airflow, removable grey
Adhesive strength	7±4N/25mm – FINAT TM 1, after 24 hours, adhered to stainless steel
Service Temp	>10°C

RELEASE BACKING	
Type	Double sided PE coated, airflow embossed
Colour/Finish	White