

Technical Fact Sheet



Digitac Floortac Outdoor SAV

Digitac Floortac Outdoor SAV is a white, deep grain embossed, anti-slip vinyl with an aluminum construction and a permanent solvent acrylic adhesive. Perfect for outdoor applications on rough wall and floor surfaces such as concrete, asphalt, brick, tiles, marble, terrazzo. The Digitac Floortac Outdoor has a R12 non-slip rating with up to 1 year outdoor life.



Application Text

- Street graphics
- Floor graphics
- Wall graphics
- Textured surfaces

Technical Fact Sheet



Important Note

All values presented in this data sheet provide the general characteristics of the product. It is the responsibility of the customer and/or end user to determine that the product is fit for the specific application it is to be used for. All values presented in this data sheet provide the general characteristics of the product. It is the responsibility of the customer and/or end user to determine that the product is fit for the specific application it is to be used for.

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of relative humidity. Do not expose to direct sunlight. The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

Technical Fact Sheet



Technical Data

Technical Fact Sheet



Test Items	Result Test Method	
Peel (N/25mm) for 20 minutes	1.4	ASTM-1000 on glass
Peel (N/25mm) for 24 hours	1.5	ASTM-1000 on glass
Peel (N/25mm) at 70°C for 24 hours	2.2	ASTM-1000 on glass
Initial Tack (ball no. 7/cm)	0.1	JIS on stainless steel
Peel Adhesion to linear (g/25mm)	19-20	PSTC-1, 30cm/min
Dimension (min), holding power	1500↑	PSTC-7

Installation:

Sweep the application surface to remove contaminants (dust, dirt, water etc.) & ensure it is completely dry.

If the surface is oily, please power wash with commercial degreaser.

Peel off the release liner, lay the vinyl flat on the surface and apply pressure over the complete surface area of the vinyl with a J-roller or hard rubber roller, rolling moving from the centre to the edge.

Make sure all edges of the film have completely adhered to the surface.

Removal:

Technical Fact Sheet



Use a putty knife (or blade) to peel up a corner, then pull the vinyl away from the surface at an angle less than 45 degrees.

No residue remains on the surface with peel-off removal.

If the graphics are installed on asphalt or other rough surfaces in locations with heavy vehicle traffic, the vinyl could be difficult to remove and may require power washing at a low angle to remove worn-in graphics

Longevity:	Suitable up to 1 year outdoor
Anti-Slip Rating	R12
Printing:	Eco-solvent, UV and Latex
Adhesive:	Permanent Solvent Acrylic
Release Liner:	Double PE coated